CIF DVR's

4/8/16CH Real-Time

SA-4100N
SA-8200N
SA-16400N

▪ Front Panel

▪ Rear Panel

SPECIFICATIONS

MODEL		SA-4100N	SA-8200N	SA-16400N
System	Compression Format	H.264		
	OS	Embedded Linux		
Video	Input	4CH,BNC(1.0Vp-p,75Ω)	8CH,BNC(1.0Vp-p,75Ω)	16CH,BNC(1.0Vp-p,75Ω)
	Standard Output	1*BNC Mainout 1*Spot 1*VGA:1280x1024,800x600,1024x768		
Audio	Audio Input	4CH		
	Audio Output	1CH		
	Two way audio	YES		
Recording	Real Time Recording	4CH CIF real time	8CH CIF real time	16CH CIF real time
	D1(4CIF)	30(NTSC)/25(PAL)fps	60(NTSC)/50PAL)fps	120(NTSC)/100PAL)fps
	CIF	120(NTSC)/100(PAL)fps	240(NTSC)/200PAL)fps	480(NTSC)/400PAL)fps
	Recording Mode	Schedule,Manual,Motion,Sensor		
Playback	Playback Channel	4CH	8CH	16CH
	Search Mode	Time ,Event,File Mangement		
Backup	USB Disk	1 USB 2.0 port		
	DVD Burner	NO		
	Backup Format	DAT or AVI		
Remote Application	Dual Stream	Master stream :1~25/30fps@4CIF/CIF Network stream:1~6/7fps@CIF		
	Browser	IE(Windows XP /2000/vista/9),Safari(Mac OS)		
	Master Stream in Network	NO		
	CMS	YES		
	3G	Super Cam/pro/HD for iPad2/iPhone/Blackberry/Android/Symbian/Windows mobile		
	User Access	10 users online with professional authority management		
Alarm	Alarm Input	4CH	8CH	16CH
	Alarm Output	1CH		
Storage	HDD	1SATA-2TB		
PTZ	PTZ	1*RS485		
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VISCA,SAMSUNG,RM110,HY		
	PTZ Control	pan,tilt,zoom,preset,cruise,trace		
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)		
	Protocol	TCP/IP,DHCP,DDNS,NTP,SMTP		
Others	Dimention	W300xD260xH55mm		
	IR Controller	x1, with IR exstention option		
	Power Supply	DC 12V/3A		
	Operating Temperature	0℃~50℃		